Amendments to the Claims

- 1. (Currently amended) A latex for dip molding, which is obtainable obtained by emulsion polymerization of 100 parts by weight of a monomer mixture in the presence of 0.5 to 10.0 parts by weight of alkyl benzene sulfonate containing at least 10 weight % of C_{13-20} alkyl benzene sulfate and a redox polymerization inhibitor containing no transition metal salt.
- 2. (Original) The latex for dip molding according to claim 1, wherein the alkyl benzene sulfonate contains at least 25 weight % of C_{13-20} alkyl benzene sulfonate.
- 3. (Original) The latex for dip molding according to claim 1, wherein the alkyl benzene sulfonate contains at least 40 weight % of C_{13-20} alkyl benzene sulfonate.
 - 4. (Cancelled)
- 5. (Currently amended) The latex for dip molding according to claim 4 1, wherein the redox type polymerization initiator containing no transition metal salt is a combination product of an oil-soluble peroxide with a reducing agent.
- 6. (Original) The latex for dip molding according to claim 5, wherein the reducing agent is an alkali metal sulfonate or ammonium sulfonate.
- 7. (Original) The latex for dip molding according to claim 6, wherein the alkali metal sulfonate is sodium formaldehyde sulfoxylate.
- 8. (Previously presented) The latex for dip molding according to claim 1, wherein 100 parts by weight of the monomer mixture comprises 15 to 45 parts by weight of a vinyl cyanide monomer, 35 to 80 parts by weight of a conjugated diene monomer, 0.1 to 20 parts by weight of

an ethylenically unsaturated carboxylic acid, and 0 to 20 parts by weight of other ethylenically unsaturated monomer copolymerizable with the above monomers.

- 9. (Previously presented) The latex for dip molding according to claim 1, wherein the emulsion polymerization of the monomer mixture is carried out in the presence of a seed polymer having an average particle diameter of 10 to 90 nm and a glass transition temperature (Tg) of -50 to 50°C obtained by emulsion polymerization of a vinyl cyanide monomer and an ethylenically unsaturated monomer copolymerizable therewith.
- 10. (Withdrawn) A dip molded product produced by dip molding from the latex for dip molding described in claim 1.
- 11. (Withdrawn) The dip molded product according to claim 10, which is a glove or a fingerstalls.